

# ITC 7



## Rugged Industrial PC with a 15" Touch Screen

- 15" TFT-Display and resistive touch screen
- All-in-one solution, 2.7" slim design
- 360° Protection IP 54
- Fast and easy service access through USB
- Extreme temperature cycles
- Extreme shock & vibration
- Fanless design

## Introduction

DLoG ITC 7 is a fully rugged all-in-one industrial PC with a particularly flat housing (2.7") and lean configuration. It is easy to operate (15" touch screen), designed for reliable implementation in rough environmental conditions

## Specification

System	CPU	Intel® Celeron® M 1 GHz Ultra Low Voltage
	Memory	512 MB up to 1 GB DDR2
	Hard disk drive	Industrial HDD: 40 GByte, other capacities on request
	CompactFlash	Type I/II up to 16 GByte
Housing		coated aluminium
		fanless design
Dimensions/Weight		326 x 395 x 70 mm / 12.83 x 15.55 x 2.75 in
		6 kg / 13.23 lbs
Display		15" Color-TFT
	Resolution	XGA 1024 x 768
Touch Screen		DLoG-specific resistive touch screen
	Durability	35 million touches in one location
Software	Operating systems	MS® Windows® XP Professional, XP Embedded Linux on request
	Emulations	VT100, VT220, IBM 5250, TN 3270
		Citrix Client®
		Freefloat Access One
Interfaces	Serial	2 x RS-232
	USB	1x COM 1, 5 V optionally 2 x USB 2.0 (HI-SPEED™)
	PS/2	keyboard/mouse
Network	LAN	Ethernet 10/100 MBit/s
Power supply	AC	110/230 VAC
Environmental	IP Protection class	360° IP 54
	Certifications	CE
	Operating temperature	0 to +50 °C / 32 to 122 °F
	Relative humidity	10 to 90% @ 40 °C / 104 °F, non condensing
	Vibration/Shock	Class 5M1 according to EN 60721-3-5

Information in this document is subject to change without prior notice. The software and hardware designations used in this text are in most cases also registered trademarks and are thus subject to law.